

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
 Product name : THOR EPOXY ACRYLATE RESIN  
 Product code : THEA380

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Main use category : Professional use, Consumer use

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

Wykamol Group Ltd.  
 Unit 3, Boran Court, Network 65 Business Park.  
 Hapton, Burnley BB11 5TH - United Kingdom  
 T +44 (0) 1282 473100  
[info@wykamol.com](mailto:info@wykamol.com) - [www.wykamol.com](http://www.wykamol.com)

#### 1.4. Emergency telephone number

Emergency number : +44 (0) 1282 473100 (0800 - 1700 UK time)

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Liq. 3	H226
Skin Irrit. 2	H315
Eye Irrit. 2	H319
Skin Sens. 1	H317
Repr. 2	H361
STOT RE 1	H372

Full text of H-phrases: see section 16

#### 2.2. Label elements

##### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

Signal word (CLP) :

Danger

Hazardous ingredients :

styrene, dibenzoyl peroxide, benzoyl peroxide

Hazard statements (CLP) :

H226 - Flammable liquid and vapour  
 H315 - Causes skin irritation  
 H317 - May cause an allergic skin reaction  
 H319 - Causes serious eye irritation  
 H361 - Suspected of damaging fertility or the unborn child  
 H372 - Causes damage to organs through prolonged or repeated exposure

Precautionary statements (CLP) :

P202 - Do not handle until all safety precautions have been read and understood  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 P233 - Keep container tightly closed  
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P332+P313 - If skin irritation occurs: Get medical advice/attention  
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention

# THOR EPOXY ACRYLATE RESIN

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

P337+P313 - If eye irritation persists: Get medical advice/attention

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
dibenzoyl peroxide, benzoyl peroxide	(CAS No) 94-36-0 (EC no) 202-327-6 (EC index no) 617-008-00-0	5 - 50	Org. Perox. B, H241 Eye Irrit. 2, H319 Skin Sens. 1, H317
styrene	(CAS No) 100-42-5 (EC no) 202-851-5 (EC index no) 601-026-00-0	5 - 20	Flam. Liq. 3, H226 Repr. 2, H361d Acute Tox. 4 (Inhalation), H332 STOT RE 1, H372 Skin Irrit. 2, H315 Eye Irrit. 2, H319

Full text of H-phrases: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Allow victim to breathe fresh air. Allow the victim to rest. Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.
First-aid measures after skin contact	: Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash with plenty of soap and water. Wash contaminated clothing before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: Danger of serious damage to health by prolonged exposure through inhalation. May cause an allergic skin reaction.
Symptoms/injuries after skin contact	: Causes skin irritation.
Symptoms/injuries after eye contact	: Causes serious eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

No additional information available

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media	: Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapour.
Explosion hazard	: May form flammable/explosive vapour-air mixture.

### 5.3. Advice for firefighters

Firefighting instructions	: Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.
Protection during firefighting	: Do not enter fire area without proper protective equipment, including respiratory protection.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking.
------------------	---

# THOR EPOXY ACRYLATE RESIN

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

### 6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.  
Emergency procedures : Ventilate area.

### 6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

### 6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Additional hazards when processed : Handle empty containers with care because residual vapours are flammable.  
Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapour. No open flames. No smoking. Use only outdoors or in a well-ventilated area. Do not handle until all safety precautions have been read and understood. Do not breathe fume, vapours.  
Hygiene measures : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep only in the original container in a cool, well ventilated place away from children, Direct sunlight. Keep container tightly closed. : Keep away from  
Incompatible products : Strong bases. Strong acids.  
Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

### 7.3. Specific end use(s)

See technical instructions for use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

THOR EPOXY ACRYLATE RESIN	
DNEL/DMEL (Workers)	
Acute - systemic effects, inhalation	1080 mg/m <sup>3</sup> Styrene
Long-term - systemic effects, inhalation	420 mg/m <sup>3</sup> Styrene

### 8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure.  
Materials for protective clothing : Wear suitable protective clothing and gloves  
Hand protection : Wear protective gloves  
Eye protection : Chemical goggles or safety glasses  
Skin and body protection : Wear suitable protective clothing  
Respiratory protection : Wear appropriate mask  
Other information : Do not eat, drink or smoke during use.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state : Liquid  
Appearance : Paste.  
Colour : Grey.  
Odour : styrene.  
Odour threshold : No data available  
pH : No data available

# THOR EPOXY ACRYLATE RESIN

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 32 °C
Auto-ignition temperature	: 480 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 1,46
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1,1 vol % 8 vol %

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Product is stable and non reactive while in cartridge. The catalyst undergoes self accelerating decomposition at and above 50 °C. The resin can solidify exothermically if heated, exposed to sunlight or air.

### 10.2. Chemical stability

Flammable liquid and vapour. May form flammable/explosive vapour-air mixture.

### 10.3. Possibility of hazardous reactions

None under normal use.

### 10.4. Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat. Sparks.

### 10.5. Incompatible materials

Strong acids. Strong bases. Oxidizing agent. metals.

### 10.6. Hazardous decomposition products

fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

THOR EPOXY ACRYLATE RESIN	
LD50 oral rat	5000 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified Based on available data, the classification criteria are not met
Carcinogenicity	: Not classified Based on available data, the classification criteria are not met
Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
Specific target organ toxicity (single exposure)	: Not classified Based on available data, the classification criteria are not met
Specific target organ toxicity (repeated exposure)	: Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	: Not classified Based on available data, the classification criteria are not met

# THOR EPOXY ACRYLATE RESIN

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

Potential adverse human health effects and symptoms : Harmful if inhaled.

### SECTION 12: Ecological information

#### 12.1. Toxicity

No additional information available

#### 12.2. Persistence and degradability

THOR EPOXY ACRYLATE RESIN	
Persistence and degradability	Not established.

#### 12.3. Bioaccumulative potential

THOR EPOXY ACRYLATE RESIN	
Bioaccumulative potential	Not established.

#### 12.4. Mobility in soil

No additional information available

#### 12.5. Results of PBT and vPvB assessment

No additional information available

#### 12.6. Other adverse effects

Additional information : Avoid release to the environment

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.  
Additional information : Handle empty containers with care because residual vapours are flammable.  
Ecology - waste materials : Avoid release to the environment.

### SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

#### 14.1. UN number

UN-No. (ADR) : 1866  
UN-No. (IMDG) : 1866

#### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : RESIN SOLUTION  
Proper Shipping Name (IMDG) : RESIN SOLUTION  
Transport document description (ADR) : UN 1866 RESIN SOLUTION, 3, III, (D/E)  
Transport document description (IMDG) : UN 1866 RESIN SOLUTION, 3, II

#### 14.3. Transport hazard class(es)

##### ADR

Transport hazard class(es) (ADR) : 3  
Danger labels (ADR) : 3



##### IMDG

Transport hazard class(es) (IMDG) : 3  
Danger labels (IMDG) : 3



# THOR EPOXY ACRYLATE RESIN

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 14.4. Packing group

Packing group (ADR) : III

Packing group (IMDG) : II

### 14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

### 14.6. Special precautions for user

#### - Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 640E

Limited quantities (ADR) : 5I

Excepted quantities (ADR) : E1

Packing instructions (ADR) : P001, IBC03, LP01, R001

Special packing provisions (ADR) : PP1

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T2

Portable tank and bulk container special provisions (ADR) : TP1

Tank code (ADR) : LGBF

Vehicle for tank carriage : FL

Transport category (ADR) : 3

Special provisions for carriage - Packages (ADR) : V12

Special provisions for carriage - Operation (ADR) : S2

Hazard identification number (Kemler No.) : 30

Orange plates :



Tunnel restriction code (ADR) : D/E

EAC code : •3YE

#### - Transport by sea

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E2

Packing instructions (IMDG) : P001

Special packing provisions (IMDG) : PP1

IBC packing instructions (IMDG) : IBC02

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP8

EmS-No. (Fire) : F-E

EmS-No. (Spillage) : S-E

Stowage category (IMDG) : B

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

# THOR EPOXY ACRYLATE RESIN

## Safety Data Sheet

according to Regulation (EC) No. 453/2010

### 15.1.2. National regulations

No additional information available

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.

Full text of H- and EUH-phrases:

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Org. Perox. B	Organic Peroxides, Type B
Repr. 2	Reproductive toxicity, Category 2
Repr. 2	Reproductive toxicity, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
H226	Flammable liquid and vapour
H241	Heating may cause a fire or explosion
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H332	Harmful if inhaled
H361	Suspected of damaging fertility or the unborn child
H361d	Suspected of damaging the unborn child
H372	Causes damage to organs through prolonged or repeated exposure

SDS EU (REACH Annex II)

*The information provided in this safety data sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information provided is designed only as guidance for safe use, processing, handling, storage, transport, release and disposal. It is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for use in combination with any other materials or in any process, unless specified in this safety data sheet.*