



COVER-IT HARDFLOOR & GLASS PROTECTOR

Self-Adhesive Protection Sheet for Glass, Resilient and Hard Floor Surfaces

Technical Data Sheet

DECORATORS RANGE



Description:

A high performance, self-adhesive protection material for covering and protecting hard floors and surfaces against mess, dirt, spillages and staining, etc. whilst painting and decorating, plastering, tiling and general building and maintenance projects. Also suitable for use on glass and windows.

Features & Benefits:

- ◆ **Self-adhesive.**
- ◆ **Low tack, temporary fix - can be removed easily.**
- ◆ **Tear resistant.**
- ◆ **Fully waterproof.**
- ◆ **Safer to use than loose dust sheets and coverings.**
- ◆ **Heavy duty.**
- ◆ **For interior use.**

Uses

For use on lacquered and plastic surfaces, aluminium, stainless steel, vinyl, hardwoods & laminates, glass, windows, hard PVC surfaces, worktops, cabinets, cills and furniture surfaces.

Limitations

- In rare circumstances, COVER-IT can leave sticky residues on certain surfaces so it is recommended test areas be carried out prior to application.
- Always check that COVER-IT is securely adhered to the surface before commencing any work to reduce slips, trips and falls.
 - Replace COVER-IT after 4 weeks. Any unexpected residue can be easily removed by hand or with Bond It MULTI-WIPES - dependant on surface, check the compatibility of any surfaces with the wipes in an inconspicuous area first. Bond It FOIL SAFE CLEANER may also be used if the surface is suitable.
 - Do not use underfloor heating whilst COVER-IT is in position or 24 hours prior to application.
 - In heavily trafficked areas or if exposed to excessive light or heat, replace at least once a week, checking for any residues left on the surface
 - Disposable - single use only.
 - Slippery when wet.

Application

Perform a compatibility test on an inconspicuous area prior to full application. Ensure the surface is free from dust, moisture and grease prior to application.

Flooring - Place the roll onto the floor with the open end facing away from the direction it is to be applied. Unpeel approx 300mm (12") of the protective cover and adhere it firmly to the surface. Simply push the roll forward slowly using either your foot or a soft



brush, making sure it follows a straight line, smoothing it out as it unwinds to eliminate air bubbles or creases. Ensure film is safely and securely positioned before commencing work.

Other Surfaces - Unpeel approx 300mm (12") of COVER-IT and adhere it to the surface firmly by hand, simply unwind the roll smoothing down as you push the roll forward covering the surface.

Glass/ Windows - this product is also suitable for use on windows when painting window frames and sills.

Removal

Easy and simple - the low tack adhesive will allow for easy removal. Lift each edge in turn and pull back towards the middle to keep any contaminants central on the roll ensuring any spills are covered and cannot escape before lifting the whole sheet.

Size

Available in rolls of 600mm widths by 25 and 50 metre lengths.

Colour

Blue plastic film.

Shelf Life

Minimum 12 months from date of manufacture.

Storage Conditions

Store in cool dry conditions between +5 and +25°C. Safe in normal

use however as a precaution keep polythene outer packaging away from children. Keep away from direct sunlight and protect from frost.

Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Dispose of in accordance with local regulations – sheet is polythene. Container is cardboard which can be widely recycled locally.

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the

user’s responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Appearance	Transparent blue polyolefin film
Adhesive	Pressure sensitive acrylic
Thickness	<28 microns
Application Temperature Limit	Between +15°C to +25°C
Commodity Code	3921909000

Product / Order Details

Code	Colour	Size	Barcode	UFI
BDCIHP25	Blue	600mm x 25M	5060021369703	-
BDCIHP50	Blue	600mm x 50M	5060021369833	-



Part of the Bond It Decorating Sundries Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.
Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com
EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson’s Quay, Dublin 2. **Tel:** +353 1 960 9411
Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Certificate Number 6152
 ISO 9001
 ISO 14001
 ISO 45001

Version 5
 : Updated 26/09/24



An **ASTRAL** Limited Company