

DECLARATION OF PERFORMANCE

DoP No: BPI-ADH-001

1. Product Type

BPI Memstick Adhesive
(Hybrid Polymer Sealant and Adhesive)

2. Intended Use

Façade sealant for interior and exterior use (F EXT-INT).
Suitable for bonding and sealing applications in construction.

3. Manufacturer

Seal It Services Ltd
Unit H4 Premier Way
Lowfields Business Park
Elland, West Yorkshire
HX5 9HF
United Kingdom

4. System of Assessment and Verification

System 3

5. Harmonised Standard

EN 15651-1:2012
EN 13501-1:2019

6. Notified Body

Notified Body No: 2538

7. Declared Performance

Essential Characteristic	Performance	Harmonised Standard
Reaction to Fire	Class E	EN 13501-1:2019
Release of Chemicals	None	See SDS
Water Tightness & Air Tightness	Pass	EN 15651-1:2012
Elastic Recovery	≥ 60%	EN 15651-1:2012
Resistance to Flow	≤ 3mm	EN 15651-1:2012
Loss of Volume	NPD	EN 15651-1:2012
Adhesion/Cohesion after water immersion	NF	EN 15651-1:2012
Secant Modulus at 23°C	≤ 4 N/mm ²	EN 15651-1:2012
Secant Modulus at -20°C	≤ 6 N/mm ²	EN 15651-1:2012
Tensile Properties at maintained extension	NF	EN 15651-1:2012
Adhesion/Cohesion at variable temperatures	NF	EN 15651-1:2012
Durability	Pass	EN 15651-1:2012

8. Declaration

The performance of the product identified above is in conformity with the declared performance.

This declaration of performance is issued in accordance with Regulation (EU) No 305/2011 as it applies in Great Britain, under the sole responsibility of the manufacturer identified above.

9. Supplied and Branded By

Building Preservation Industries (BPI)



This product is manufactured by Seal It Services Ltd and supplied under the BPI brand. Performance data is based on manufacturer certification.